

VALVOLE FORGIATE

SARACINESCA - DISCO - RITEGNO



VALVOLE FORGIATE - GATE- GLOBE- CHECK

Design: API 602, ISO 15761-BS 5352

Rating in accordo ad ANSI B16.34 per classi: 150÷ 4500 lb; ad API 602 per classe 800

- Sizes: 1/4" a 2"
- Marcatura: MSS SP25
- OS&Y: Outside Screw and Yoke
- SW End: in accordo ad ANSI B16.11
- NPT END: in accordo ad ANSI B1.20.1
- BW END: in accordo ad ANSI B16.25
- FLG END: in accordo ad ANSI B16.5
- FACE TO FACE: in accordo ad ANSI B16.10
- CORPO COPERCHIO: imbullonato o saldato
- PASSAGGIO: totale o ridotto
- TEST: API 598 e particolari richieste del cliente



MATERIALI STANDARD E CUSTOMIZZATI

A105	A182 F304L	B564 N06625
A350 LF2	A182 F316	B564 N10665
A694 F60	A182 F316L	B574 N06022
A350 LF3	A182 F317L	B564 N10276
A182 F5	A182 F321	A182 F51
A182 F11	A182 F347	A182 F53
A182 F22	A564 630	A182 F44
A182 F9	B564 N04400	B625 N08904
A182 F6A	B564 N08810	B381 F2
A182 F304	B564 N06600	

TIPOLOGIE SPECIALI

Extended Body
Bellows Sealed
Cryogenic Service