

VALVOLE FUSE - GATE - DISCO - CHECK



VALVOLE FUSE A SARACINESCA BW-FLG

Design: API 600

- Sizes: maggiori di 1 ½"
- Serie: ANSI 150÷2500
- OS&Y: Outside Screw & Yoke
- FACE TO FACE: ANSI B16.10
- FLANGE FACE: ANSI B16.5
- BW END: ANSI B16.25
- CORPO-CAPPELLO: imbullonato o saldato
- Test: API598



VALVOLE FUSE A DISCO BW-FLG

Design: BS 1873 & BS 5352

- Sizes: maggiori di 1 1/2"
- Serie: ANSI 150÷2500
- OS&Y: Outside Screw & Yoke
- FACE TO FACE: ANSI B16.10
- FLANGE FACE: ANSI B16.5
- BW END: ANSI B16.25
- CORPO-CAPPELLO: imbullonato o saldato
- Test: API598

VALVOLE FUSE DI RITEGNO BW-FLG

Type: Swing, Piston, Tilting, Dual Plate
Design: API 6D, API 594

- Sizes: maggiori di 1.1/2"
- Marcatura: MSS SP25
- Bw End: in accordo ad ANSI B16.25
- FLG END: in accordo ad ANSI B16.5
- Face to Face: in accordo ad ANSI B16.10
- Corpo Coperchio: imbullonato o saldato



MATERIALI STANDARD E CUSTOMIZZATI

A216 WCB	A351 CF3	A494 CW6M
A352 LCB	A351 CF8M	A494 CX2MW
A352 LC3	A351 CF3M	A494 CW12 MW
A217 C5	A351 C68M	A890 Gr 4A
A217 WC6	A351 CF8C	A890 Gr 6A
A217 WC9	A494 M35-1	A351 CK3MCuN
A217 C12	A494 CY40	B367 C2
A351 CA15	A494 CW 6MC	
A351 CF8	A494 N 12MV	

TIPOLOGIE SPECIALI

Bellows Sealed
Cryogenic Service